

GVWR 15,000 lb.

Capacity 11,050 lb. With 1,000 lb Hitch Load

Empty Weight: 3,950 lb.

- 7,000 lb. Dexter Brand Braking Axles with Slipper Suspension
- 235/80 R16 Load Range E 10 Ply Westlake Radial Tires
- 8" Channel Main Frame, Uprights & Neck
- 3x3 Tubing Dump Box Frame - 3" Channel Crossmembers on 16" Centers
- 10 Gauge Floor - 12 Gauge Walls
- 30" Headboard - 24" Sides - Raised Rear Corner Post with Lumber Gussets (Allows You to Extend Your Wall Height)
- 83" Inside Width
- Lockable Toolbox with Tool Divider
- Scissor Hoist with 5" x 21.5" Cylinder (Power Up Power Down)
- (4) D-Rings Mounted to Wall on Inside of Dump Bed
- Tarp System With Aluminum Pull Bar
- US Made Pump With 20' Hand Remote, (Optional Wireless Remote) - Deep Cycle Battery
- Two Way Tailgate Opens for Dumping Bulk Materials or Can Be Set in Spreader Mode
- HD 80" Long - 4" Channel Easy Access Slide-In Loading Ramps. Capacity #12,000
- Spare Tire Mount
- Adjustable Gooseneck Coupler
- 12,000 lb. Drop Leg Jack
- DOT Approved Safety Chains, Break-a-Way Switch and DOT Tape
- Sealed US Made Wiring Harness with LED Lighting
- Phosphate Washed, Primed with Epoxy Primer and Two Coats of Polyurethane Paint



Available Lengths:

83" x 14' - \$ _____

83" x 16' - \$ _____

